



## 4x2 / ELECTRIC



Shown with optional accessories.

HOOD COLORS	
FACTORY-INSTALLED PACKAGES	Trail / Cruiser
TIRE OPTIONS	Max Terrain (Standard) / Trail Rider / Cruiser / Turf / Gladiator
BED OPTIONS	Poly Bed, Large Steel Bed, Flip Seat / Steel Bed
POWER / MOTOR	25hp, 18kW - AC motor, 48V Lithium-Ion Battery, 600 amp Controller
SPEED / RANGE	30 mph (24 mph with Rear Flip Seat) / Up to 50 Miles
ELECTRONIC POWER STEERING	Included
BED CAPACITY	400 lbs / 600 lbs (with HD Shocks)
TOW	1,500 lbs





## 4x2 / ELECTRIC

## THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The Easy Life Warranty from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. As long as you care for your machine like you should, don't wreck it, or crush it, we're going to cover it. Except for tires, brake pads, batteries, damage, neglect. That's the limit. Visit Landmaster.com to learn more.

POWER / MOTOR	24 hp (18.0 kW) with 71.5 ft lbs torque rating — AC Motor powered by a 48V Lithium-lon battery powerplant (5.0kW or 8.0kW)
SEATING CAPACITY	4 Person
SPEED	30MPH (24MPH with Rear Flip Seat)
FUEL CONSUMPTION	N/A
RANGE	Up to 50 miles ( 160 ah battery)*
STARTING	Keyed on/off
BATTERY	48V 160AH Lithium-lon
SPARK PLUG	N/A
FUEL CAPACITY	N/A
ALTERNATOR	Converter / 30 amps
TRANSMISSION	Direct drive
TRANSAXLE	Model 24 Schafer
DIFFERENTIAL	Cable Activated Locking
DRIVE	2wd
FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
BRAKE SYSTEM	4 wheel disc, hydraulic brake
TIRES	25" Standard Max-Terrain HD D0T / Radial 8 Ply Tires on 12" Steel Wheels
DIMENSIONS	127" L x 58" W x 76" H (with poly bed)**
WHEEL BASE	105"
TURNING RADIUS	14'
GVWR	2,530 lbs.
CURB WEIGHT	1,530 lbs. with 160 AH battery
BED MATERIALS	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 400 lbs. / HD L-ROSS - 600 lbs.
TOWING CAPACITY	1,500 lbs.
TOTAL PAYLOAD	1,000 lbs.
WARRANTY	1 year motor / all other 1 year limited, 5 year prorated Lithium battery
ADDITIONAL FEATURES	On-board charger, 3pt lap/ shoulder belts for driver & passenger, 12V/18W LED headlights, 2" rear and front receiver hitch, welded steel frame, Single 12V auxiliary outlet for accessories, polyurethane powder paint. Complete weather-sealed wiring connections. Wide slection of additional accessories available along with three bed options. In-dash, hour meter standard. LED true state of charge meter for the 48 volt system is standard. Low charge audible warning. Battery shut down switch. Electric accelerator pedal.

<sup>\*</sup> Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances. \*\*Overall vehicle dimensions may vary with the addition of optional accessories